

# **CARETECH DILUTION SET**



The Caretech Dilution Set has been designed to connect directly to any freshwater source to On-Line dilute any water-based Marine Care cleaning product.

The suction of the pump: can be connected to a 600 or 1000 litres IBC, or can draw from any type of product drum.

Pump capacity 2000 litres per hour!

Optional: (Ex) certificate and earth lug.

MARINE CARE SCANDINAVIA AS Tveiteraasveien 12, 5232 Paradis Bergen, Norway T. +47 55 51 05 00 F. +47 92 03 62 06

F. +47 92 03 62 06 E. operations@marinecare.no W. www.marinecare.no

# **CARETECH DILUTION SET**

# **Technical specifications**

### STAINLESS STEEL PANEL/BRACKET

Material AISI 304: 2 mm

#### **BALL VALVE**

Material AISI 316Suction/discharge 3/4" BSP Male

#### FRESH WATER FILTER 5"

Material Techno polymer
 Suction/discharge 3/4" BSP Female
 Capacity 3000 litres/hour
 Filter mesh 60 micron (µm)

#### **WATERP RESSURE REGULATOR**

Material Brass, Nickle plated

Suction/dischargeCapacity3/4" BSP Female3000 litres/hour

Max. pressure IN 25 bar
Adjustable pressure 1 - 6 bar
Pre set pressure 3 bar

#### WATER DRIVEN PISTON PUMP

Capacity 10 - 2000 litres/hour

Water pressure 0,5 - 4 bar
Dilution rate 5 - 25 %

• Suction/discharge 3/4" BSP Female/Male

#### **CONNECTIONS**


Fresh Water IN
Water product mixture
3/4" PP Camlock Male
PP Camlock Male

Product suction SN60 x 6 PE Female

## **OPTIONAL SPRAY GUN SET COMPLETE WITH HOSE**

Spray gun 1/2" 1500 litres per hour
Spray pattern adjustable
Hose, incl. connectors 1/2" 30 meters





Optional: (Ex) certificate and earth lug. Concentrated additive to be dosed

Marine Care Scandinavia AS
Tveiteraasveien 12,
5232 Paradis
Bergen, Norway
T. +47 55 51 05 00
F. +47 92 03 62 06
E. operations@marinecare.no
W. www.marinecare.no