

Liquid cleaning agent for removal of (partially) carbonized oil residues

- Non corrosive
- Highly concentrated
- Approved by: > Marinfloc

## **DESCRIPTION**

Careclean Filter is a liquid blend of solvents and alkali. The product is used for cleaning of carbonized permanently fixed oil coolers, oil pre-heaters and metal/ceramic oil filters.

# **ADVANTAGE**

Careclean Filter is a highly concentrated product that removes (partially) carbonized oil and tarlike deposits from ferro and non ferro metals. Timely/regular cleaning prevents the formation of coke-like adherents.

## **APPLICATION**

Careclean Filter is used for the cleaning of permanently fixed oil coolers, oil pre-heaters and metal/ceramic oil filters. These units are regularly contaminated by particles and partially carbonized oils.

Timely cleaning prevents the formation of coke-like adherents which are difficult or impossible to remove.

#### Immersion baths

Put the filters in a steel bath filled with undiluted Careclean Filter and let them soak, depending on the degree of contamination for 2 to 10 hours. Take out the components and flush clean with a powerful waterjet.

## **DIRECTIONS FOR USE**

Careclean Filter is used undiluted at cleaning temperatures not exceeding 60 °C. The cleaning effect is obtained by filling and/or circulating the product. Cleaning will take 8 up to 24 hours depending upon the degree of contamination.

MARINE CARE BV Mozartlaan 3 3144 NA Maassluis The Netherlands +31 (0)10 2950342 +31 (0)10 2950345 supply@marinecare.nl W. www.marinecare.nl Circulation undiluted Immersion bath undiluted

**PROPERTIES** 

Article number 14109

pH Not applicable
Density 1,12 g/cm³
Flashpoint 81 °C

Physical state

**APPROVALS** 

Marinfloc Approved OWS Compatible

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

Liquid



# CARECLEAN FILTER

- Non corrosive on metals
- Highly concentrated
- Approved by:Marinfloc

