

CARECLEAN GP ENVIRO

A water based general purpose degreaser for engine room, rig washing and deck cleaning.

DESCRIPTION

Careclean GP Enviro is a water based general purpose cleaner, with excellent degreasing properties.

ADVANTAGE

- biodegradable, non-toxic, waste water will split into an oil/water phase
- clean, fresh odor
- retains strong degreasing properties when diluted
- leaves no film residues on cleaned surfaces
- suitable on most common metals and coatings
- suitable for use in conjunction with oil water separators
- contains no petroleum solvents, non-flammable

APPLICATIONS

Careclean GP Enviro is used for engine rooms, decks, bulkheads, heavily soiled surfaces on oil installations, drilling deck, equipment and engine room accommodation. The product can be used on all materials, like ferro and non ferro metals, plastics, rubbers, coatings and lacquers.

DIRECTIONS FOR USE

For heavy contamination

Careclean GP Enviro is applied by spraying undiluted and left for 20 - 60 minutes. It must then be hosed off with a powerful waterjet, whilst brushing the surfaces.

General Cleaning

Careclean GP Enviro can be diluted to a 2 % solution in water for average cleaning. It must be allowed to soak for 1 - 15 minutes before rinsing with a waterjet. The effectiveness of the product is increased by using water at a temperature of 20 up to 80 °C for product dilution and rinsing.

- Eco-friendly
- Biodegradable
- Non Toxic
- Water based
- Heavy duty Rig-Wash
- Approved by:
 - > IMO
 - > Marinfloc
 - > Coating manufacturers

discover the differ-



Tank Cleaning

Before cleaning with Careclean GP Enviro it is recommended to prewash with hot water. For drying or semi-drying oils a prewash with cold water should be carried out immediately after discharge of cargo to retard oxidation and hardening of oil residues. After 1 cycle slowly start to increase water temperature to increase effectiveness of the prewash.

DOSAGE

General Cleaning	2 % solution in freshwater
Spraying	undiluted

PROPERTIES

Article number	14101 / 16101
pH (1 % solution)	9,3 - 9,7
Density	0,99 g/cm ³
Flashpoint	None
Physical state	Liquid

APPROVALS

- IMO approved in accordance with MEPC 590
- Marinfloc Approved OWS Compatible
- Major coating manufacturers

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

CARECLEAN GP ENVIRO

- Eco-friendly
- Biodegradable
- Non Toxic
- Water based
- Heavy duty Rig-Wash
- Approved by:
 - > IMO
 - > Marinfloc
 - > Coating manufacturers

discover the differ-

MARINE CARE BV
Mozartlaan 3
3144 NA Maassluis
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. supply@marinecare.nl
W. www.marinecare.nl