

# CARETREAT ECONOMIZER

**Prevents soot deposits and low temperature corrosion in exhaust gas systems**

- Improves efficiency
- Prevents LTC
- Reduces black smoke during maneuvering
- Easy to apply

## DESCRIPTION

Caretreat Economizer is a liquid blend of catalysts and neutralizing agents, that prevents soot built-up on the heat exchanger, in the exhaust gas boilers and low temperature corrosion in the exhaust gas system.

Due to ships sailing on reduced speed in combination with low fuel quality the amount of soot in the exhaust gas has increased. Because of the low gas flow, the soot particles can easily settle on the heat exchanger fins. This results in decreasing exhaust gas boiler efficiency and decreasing engine efficiency. Caretreat Economizer prevents low temperature corrosion by neutralizing sulfuric acid.

## ADVANTAGES

- Complete coverage of entire exhaust gas system
- Improved exhaust gas boiler and engine efficiency
- Neutralizes sulfuric acid
- Prevents low temperature corrosion LTC
- Reduces fire risk in the exhaust gas boiler
- An easily dosed liquid

## APPLICATION

Caretreat Economizer is a specially developed liquid which is easily dosed into the system, using a special Marine Care injection unit. The air assisted nozzles create a fine mist. The liquid vaporizes on contact with the hot exhaust gas. The exhaust gas temperature should be above 200 °C. The active material reacts with the soot particles to create light, dry and non-adherent soot particles that easily pass the heat exchanger in the exhaust gas boiler. The resulting deposit is friable and can be easily removed by conventional sootblowing.

discover the difference



#### DIRECTIONS FOR USE:

In case the exhaust gas boiler is heavily fouled, waterwash the heat exchanger with an alkali solution, for example Careclean Alkaline or Alkaline Extra.

Caretreat Economizer is injected undiluted, with an air assisted nozzle down stream in the exhaust gas line direct after the turbo charger discharge.

#### INJECTION SYSTEMS

*Marine Care* offers a complete range of EGT Exhaust gas treatment dosing systems customized for your engine type.

#### DOSAGE

Daily 1 - 2 liters per 1000 m<sup>2</sup> of exhaust gas boiler heat exchanger surface.

#### PROPERTIES

Article number	14504
pH (1 % solution)	7
Density	1,31 g/cm <sup>3</sup>
Flashpoint	Not applicable
Physical state	Liquid

#### APPROVALS

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

#### CARETREAT ECON- OMIZER

- Improves efficiency
- Prevents LTC
- Reduces black smoke during maneuvering
- Easy to apply

discover the difference

MARINE CARE BV  
Mozartlaan 3  
3144 NA Maassluis  
The Netherlands  
T. +31 (0)10 2950342  
F. +31 (0)10 2950345  
E. [supply@marinecare.nl](mailto:supply@marinecare.nl)  
W. [www.marinecare.nl](http://www.marinecare.nl)